

TYPE OF CONTAINER AND GENERAL USE	SIZE	WEIGHT*			INTERNAL DIMENSIONS			DOOR OPENING		VOL. m ³ ft. ³	Notes	
		Kilograms		Lbs.	Millimeters		feet/inches		Millimeters			feet/inches
		Max. Gross Wt.	Tare Wt.	Max. Payload	Length	Width	Height	Width	Height			Capacity
Feet												
 Dry Van/General Suitable for commodities in bundles, cartons, boxes, loose cargo, furniture, etc.	20	24,000 52,910	2,200 4,850	21,800 48,060	5,902 19' 4 23/64"	2,350 7' 8 33/64"	2,392 7' 10 11/64"	2,341 7' 8 11/64"	2,280 7' 5 49/64"	33,2 1' 172	All steel construction.	
	40	30,480 67,200	3,800 8,380	26,680 58,820	12,032 39' 5 45/64"	2,350 7' 8 33/64"	2,390 7' 10 7/64"	2,338 7' 8 3/64"	2,280 7' 5 49/64"	67,6 2,387		
 High Cube Same as dry containers, but higher volume capacity.	40	30,480 67,200	3,900 8,600	26,580 58,600	12,033 39' 5 47/64"	2,350 7' 8 33/64"	2,695.5 8' 10 1/8"	2,338 7' 8 3/64"	2,585 8' 5 49/64"	76,2 2,690	Steel	
	20	24,000 52,910	2,140 4,717	21,860 48,192	5,894 19' 4 1/8"	2,344 7' 8 5/16"	2,347 7' 8 3/8"	2,336 7' 7 15/16"	2,275 7' 5 1/2"	31,5 1' 112	Steel	
 Open Top Suitable for high large piece cargo that cannot be loaded through container doors such as machinery, sheet glass, marble, building materials and lumber.	40	30,480 67,200	3,700 8,158	26,780 59,049	12,027 39' 5 1/2"	2,344 7' 8 5/16"	2,347 7' 8 3/8"	2,336 7' 7 15/16"	2,275 7' 5 1/2"	67,0 2,365,6		
	 Bulk Designed for the carriage of all dry free flowing materials such as chemicals, powders and granules, cement fertilizers, flour, milk powder, sugar, salt and granular plastic products.	20	24,000 52,910	2,800 6,180	21,200 46,340	5,888 19' 4"	2,332 7' 8"	2,338 7' 9"	2,340 7' 8"	2,263 7' 5"	32,4 1' 144	Steel and fiberglass coated
 Flat Used for carrying awkward and oversize loads such as machinery, cables, drums, sheet and steel coils, heavy vehicles, timber and forest products.		20	25,400 56,000	3,080 6,790	22,320 49,210	5,988 19' 7 3/4"	2,398 7' 10 3/8"	2,231 7' 7 3/8"				Steel
	40	45,000 99,202	5,300 11,683	39,700 87,518	12,064 11,662 between headers between posts	2,369 2,179 deck width between stanchions	1,943 loading height					
 Open Side Suitable for cargo that consist of large pieces that cannot be loaded through container doors. Convenient for loading/unloading at railway sidings.	20	25,400 56,000	2,930 6,460	22,470 49,540	5,896 19' 4 1/8"	2,310 7' 6 15/16"	2,255 7' 4 49/64"	2,236 7' 8 3/64"	1,960 6' 5 5/32"	31,0 1094,5	Steel	
	 Reefer Suitable for transporting perishable cargo such as vegetables, fruit, meat, etc.	20	25,400 56,000	2,870 6,330 without generator	22,530 49,670 without generator	5,460 17' 10 3/4"	2,240 88 1/16"	2,225 87 1/2"	2,240 88 1/6"	2,180 85 5/8"		Aluminum
40		32,500 71,650	4,535 9,998	27,965 61,652	11,550 37' 10 1/2"	2,250 88 1/2"	2,215 87 1/2"	2,250 88 1/2"	2,160 85"		Aluminum & Stainless Steel	
 ISO Tank IMO 1: Suitable for hazardous substances such as toxic, corrosive, highly flammable liquids. Non-hazardous tanks: Suitable for oils, plasticizers, resins, natural or synthetic latex, milk, still beers, wine, mineral water.	20	30,480 67,200	3,070 6,768	27,410 60,425						21,000 liters 5,547 US gallons	Stainless Steel	

* The dimensions and weights are based on plant manufacturers' specifications. Tolerance factors must always be taken into account by the shipper.

EXTERNAL DIMENSIONS

SIZE	Length	Width	Height	High Cube height
20	Length	6,058 mm	19' 10 1/2"	
	Width	2,438 mm	8'	
	Height	2,591 mm	8' 6"	
	High Cube height			
40	Length	12,192 mm	40'	
	Width	2,438 mm	8'	
	Height	2,591 mm	8' 6"	
	High Cube height			2,896 mm 9' 6"